



Straight 1/2" Pitch Belting HDS605 TT (HDS Texture Top)



Description

- 1/2 inch pitch
- Texture top easy release surface bullet
- Built to USDA & FDA standards
- Bi-directional
- 3/4 inch (19.1 mm) diameter nosebar capability
- Connecting rod diameter = 0.156 inch (4.0 mm)
- Standard belt width increments = 1 inch (25.4 mm) nominal, starting from 5 inches (127 mm)
- Non-standard widths available in 1/2 inch (12.7 mm) increments starting at 3 inches (76.2 mm) upon request
- Material selection may affect belt width — please contact your local partner for actual dimensions



Belt data

Belt material		PP	PE	POM
Rod material		PP	PE	PP
Nominal tensile strength F_N^1 straight run	N/m	7297	5838	14594
	lb/ft	500	400	1000
Temperature range	°C	10 - 99	-45 - 66	10 - 93
	°F	50 - 210	-50 - 150	50 - 200
Belt weight m_B	kg/m ²	4.4	4.9	5.9
	lb/sqft	0.90	1.00	1.20
Standard belt color		white	white	white

Additional belt colors and materials available, abrasive resistant Nylon (Polyamide) rods available – contact your local partner.

All data are approximate values according to KVP Inc. standard operating procedures.

Product liability, application considerations

If the proper selection and application of Habasit products are not recommended by an authorized Habasit sales specialist, the selection and application of Habasit products, including the related area of product safety, are the responsibility of the customer.

All indications / information are recommendations and believed to be reliable, but no representations, guarantees, or warranties of any kind are made as to their accuracy or suitability for particular applications. The data provided herein are based on laboratory work with small-scale test equipment, running at standard conditions, and do not necessarily match product performance in industrial use. New knowledge and experiences can lead to modifications and changes within a short time without prior notice.

BECAUSE CONDITIONS OF USE ARE OUTSIDE OF HABASIT'S AND ITS AFFILIATED COMPANIES CONTROL, WE CANNOT ASSUME ANY LIABILITY CONCERNING THE SUITABILITY AND PROCESS ABILITY OF THE PRODUCTS MENTIONED HEREIN. THIS ALSO APPLIES TO PROCESS RESULTS / OUTPUT / MANUFACTURING GOODS AS WELL AS TO POSSIBLE DEFECTS, DAMAGES, CONSEQUENTIAL DAMAGES, AND FURTHER-REACHING CONSEQUENCES.